

Standard PU Glue Injection Machine

Internal Product ID: ENFT-LVAF-007

Unit of Measurement	台
Brand	ENFT
Place of Origin	China
Certification	Manufactured Under Strict Quality Control
Min. Order Qty	1 Unit
Supply Ability	100 Sets/Month
Delivery Time	45 Days After Receipt of Advance Payment

Overview

Standard PU glue injection machine for panel filter PU gluing process, featuring servo drive and water cleaning system.

Description

Process Name: PU Glue Injection Process

Equipment Parameters:

Panel Filter (Moving Table) Standard Configuration

- 1. Total discharge rate: 8-20 g/s, designed mixing ratio A:B = 100:20 to 60;
- 2. Maximum effective size of the square automatic pouring machine: 800x600 (mm); uses servo acceleration/deceleration to drive the ball screw, achieving table movement mode;
- 3. Total machine power: 6KW;
- 4. Power supply voltage: 380V, 50Hz;
- 5. Control system uses host computer and motion control hybrid programming, with the metering pump controlled by a servo motor;
- 6. Equipped with an all-in-one PC, massive data storage;
- 7. Foot switch control or automatic control of the glue injection process;
- 8. Simple one-key operation, reducing dependence on skilled workers;
- 9. Water cleaning, environmentally friendly and reduces cleaning costs.
- 10. Dimensions: 2000*1300*1700 (mm)
- 11. Weight: 470KG

Note: Can be shared with heavy-duty truck air filters.