

End Cap Gluing Machine Production Line (PU Glue)

Internal Product ID: ENFT-HDAF-012

Unit of Measurement	台
Brand	ENFT
Place of Origin	China
Certification	Manufactured Under Strict Quality Control
Min. Order Qty	1
Supply Ability	100 Sets/Month
Delivery Time	45 Days After Receipt of Advance Payment

Overview

Production line used for end cap PU gluing, categorized as PU air filter production equipment.

Description

Process Name: End cap PU gluing

Note: PU air filter production equipment

Equipment Parameters:

Panel filter (moving table) standard configuration

- 1. Total discharge rate: 8-20 g/s, designed mixing ratio A:B = 100:20 to 60;
- 2. Max effective size of square automatic pouring machine: 800x600 mm; uses servo acceleration/deceleration to drive ball screw for table movement;
- 3. Total Power: 6KW;
- 4. Power Supply Voltage: 380V, 50Hz;
- 5. Control system uses PC and motion control hybrid programming, with metering pump controlled by servo motor;
- 6. Equipped with an all-in-one PC, massive data storage;
- 7. Foot switch control or automatic control of the gluing process;
- 8. Simple one-key operation, reducing dependence on skilled workers;
- 9. Water cleaning, environmentally friendly and reduces cleaning costs;
- 10. Dimensions: 2000*1300*1700 mm;
- 11. Weight: 470KG.