

Standard PU injection main machine

Internal Product ID: ENFT-HDAF-016

Unit of Measurement	set
Brand	ENFT
Place of Origin	China
Certification	Manufactured Under Strict Quality Control
Min. Order Qty	1
Supply Ability	100 Sets/Month
Delivery Time	45 Days After Receipt of Advance Payment

Overview

Standard PU injection main machine for PU injection process, featuring plate type (workbench moving) standard configuration.

Description

Plate type (workbench moving) - Standard configuration

1. Total discharge speed: 8 - 20 beads/second, designed mixing ratio A:B = 100:20 to 60:1;
2. The maximum effective size of the square automatic glue injection machine is 800×600 (mm). The servo motor drives the ball screw at a reduced speed to realize the random movement mode of the workbench;
3. Glue pump power: 6KW;
4. Power supply voltage: 380V, 50Hz;
5. The control system adopts integrated programming of machine and motion control, among which the metering is controlled by the upper computer;
6. The glue machine is equipped with an all-in-one machine with heavy-duty data storage;
7. Foot switch control or automatic control of the glue injection process;
8. Foolproof operation, reducing dependence on skilled workers;
9. Water cleaning, which can also reduce cleaning costs;
10. Overall dimensions: 2000×1300×1700 (mm);
11. Weight: 470KG.

Shandong Ennafente Automation Equipment Co., Ltd.

Mr.MARK: +8616678216123 | Mr. MA: +201063142001 | WhatsApp: +8616678216123 | Email: info@enftco.com

First Industrial Area, Bincheng District, Binzhou City, Shandong Province, China

Facebook: facebook.com/share/179Pi3ramf Instagram: instagram.com/enft6688 LinkedIn: linkedin.com/in/ennafente-for-car-filter-machine-7b3925369 YouTube: youtube.com/@ennafente TikTok: tiktok.com/@enftco?is_from_webapp=1&sender_device=pc X: x.com/ENFT6688 Threads: threads.com/@enft6688 Telegram: enftco.com/en/contact

WeChat



MR MA



MR MARK