

Injection moulding machine

Internal Product ID: ENFT-FMM-028

Unit of Measurement	Set
Brand	ENFT
Model Number	TC-1500-1S
Place of Origin	China
Certification	Manufactured Under Strict Quality Control
Min. Order Qty	1
Supply Ability	100 Sets/Month
Delivery Time	45 Days After Receipt of Advance Payment

Overview

Model TC-1500-1S injection moulding machine.

Description

Technical Specifications:

- Model: TC-1500-1S
- Screw Diameter: 50; 55; 60mm
- Maximum Injection Pressure: 1918; 1554; 1284kg/cm²
- Theoretical Shot Volume: 432; 522; 622cm³
- Maximum Shot Weight (PS): 393; 475; 566g
- Injection Rate: 302; 365; 435cm³/sec
- Screw Speed: 0-185r/min
- Screw Stroke: 220mm
- Nozzle Retraction Stroke: 315mm
- Number of Temperature Control: 4
- Clamping Force: 1470(150)ton
- Space Between Tie-Bar: 650*620mm
- Minimum Mold Thickness: 260(360)mm
- Opening Stroke: 300mm
- Open Daylight: 560(660)ton
- Ejector Force: 39.2(4)mm
- Ejector Stroke: 110mm
- Slidable Journey: 750mm
- Overall of Slipform (Hxv): 750*630mm
- Max. Hydraulic Pressure: 13.7(140)kg/cm²
- Pump Output: 116L/min
- Oil Tank Capacity: 425L
- Electric Power: 18.5KW
- Barrel Heating Power: 12.5kw
- Total Wattage: 31KW
- Machine Dimension (Approx.): 3.3*1.3*3.5m
- Weight: 7.5t